In re: Johansson et al.

Serial No.: 10/047,85

Filed: January 15/2002 Page 2 MAY

The following Listing will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1. (Currently Amended) A method of configuring a wireless base station of a wireless mobile data communications system, the method comprising:

determining a port number and/or an internet address to be assigned to the wireless base station;

communicating a datagram including the assigned port number and/or internet address in a destination field of a header of the datagram from a controller of the wireless mobile data communications system to the wireless base station via a backbone network of the wireless mobile data communications system; and

responsive to receipt of the datagram at the wireless base station, configuring the wireless base station to accept datagrams addressed to the assigned port number and/or internet address.

2. (Canceled)

3. (Currently Amended) A method according to Claim 1, wherein communicating a datagram including the assigned port number and/or internet address <u>in a destination field of a header of the datagram</u> from a controller of the wireless mobile data communications system to the wireless base station via a backbone network of the wireless mobile data communications system comprises:

communicating the datagram including the assigned port number and/or internet address to a router of the backbone network;

routing the received datagram to an interface between the router and the wireless base station.

Page 3

- 4. (Currently Amended) A method according to Claim 3, wherein communicating a datagram including the assigned port number and/or internet address in a destination field of a header of the datagram from a controller of the wireless mobile data communications system to the wireless base station via a backbone network of the wireless mobile data communications system further comprises communicating the routed datagram to the wireless base station via a frame relay connection between the wireless base station and the router.
- 5. (Currently Amended) A method according to Claim 3, wherein communicating a datagram including the assigned port number and/or internet address <u>in a destination field of a header of the datagram</u> from a controller of the wireless mobile data communications system to the wireless base station via a backbone network of the wireless mobile data communications system comprises communicating the datagram according to one of TCP, UDP, or TP4.
- 6. (Currently Amended) A method according to Claim 3, wherein communicating a datagram including the assigned port number and/or internet address in a destination field of a header of the datagram from a controller of the wireless mobile data communications system to the wireless base station via a backbone network of the wireless mobile data communications system comprises communicating the datagram according to one of IP or CNLP.
- 7. (Original) A method according to Claim 1, wherein the wireless mobile data communications system comprises a Cellular Digital Packet Data (CDPD) system, and wherein the wireless base station comprises a Mobile Data Base Station (MDBS).
- 8. (Original) A wireless base station for use in a wireless mobile data communications system, the wireless base station comprising:

a radio communications unit operative to communicate radio signals to and from mobile terminals; and

Page 4

Carry.

a mobile data communications interface coupled to the radio communications circuit and configured to connect to a node of a backbone network of the wireless mobile data communications system, the mobile data communications interface including a self-configuring network interface operative, responsive to receipt of a datagram from node of the backbone network including an assigned port number and/or a network address, to configure itself to accept datagrams addressed to the assigned port number and/or internet address over the backbone network.

- 9. (Original) A wireless base station according to Claim 8, wherein the self-configuring network interface is operative, responsive to receipt of a datagram from the node of the backbone network including a port number and/or network address in a destination field thereof, to configure itself to accept datagrams addressed to the included port number and/or internet address.
 - 10. (Original) A wireless base station according to Claim 8, wherein self-configuring network interface is operative to receive the datagram including a port number and/or network address therein over a frame relay connection between the wireless base station and a router of the backbone network of the wireless mobile data communications system.
 - 11. (Original) A wireless base station according to Claim 8, wherein the assigned port number and/or internet address comprises one of a TCP port number, a UDP port number, a TP4 port number, an IP address or a CNLP address.
 - 12. (Original) A wireless base station according to Claim 8, wherein the wireless mobile data communications system comprises a Cellular Digital Packet Data (CDPD) system, and wherein the wireless base station comprises a Mobile Data Base Station (MDBS).

Page 5

13. (Currently Amended) A controller for a wireless mobile data communications system, the controller comprising:

means for determining a port number and/or an internet address assigned to a wireless base station of the wireless mobile data communications system; and

means for transmitting a datagram including the assigned port number and/or internet address in a destination field of a header of the datagram to the wireless base station via a backbone network of the wireless mobile data communications system.

14. (Canceled)

- for transmitting a datagram including [[a]] the assigned port number and/or internet address for assignment in a destination field of a header of the datagram to the wireless base station via a backbone network of the wireless mobile data communications system comprises means for transmitting the datagram including the assigned port number and/or internet address to a router of the backbone network.
 - 16. (Original) A controller according to Claim 13, wherein the assigned port number and/or internet address comprises one of a TCP port number, a UDP port number, a TP4 port number, an IP address or a CNLP address.
 - 17. (Original) A controller according to Claim 13, wherein the means for selecting and the means for transmitting comprise a Network Management System (NMS) node of a Cellular Digital Packet Data (CDPD) system.
 - 18. (Currently Amended) A wireless base station, comprising:

means for receiving a datagram including an assigned port number and/or internet address for the wireless base station in a destination field of a header of the datagram; and

means for configuring the wireless base station to accept datagrams addressed to the assigned port number and/or internet address in the received datagram.

Page 6

- 19. (Original) A wireless base station according to Claim 18, wherein the wireless base station comprises a Mobile Data Base Station (MDBS) of a Cellular Digital Packet Data (CDPD) system.
- 20. (Currently Amended) A computer program product for configuring a wireless base station of a wireless mobile data communications system, the computer program product comprising program code embodied in a computer-readable storage medium, the computer program code comprising:

program code for selecting a port number and/or an internet address for assignment to a wireless base station (wireless base station) of the wireless mobile data communications system; and

program code for transmitting a datagram including the assigned port number and/or internet address in a destination field of a header of the datagram to the wireless base station via a backbone network of the wireless mobile data communications system.

21. (Canceled)

- 22. (Currently Amended) A computer program product according to Claim 20, wherein the program code for transmitting a datagram including [[a]] the assigned port number and/or internet address in a destination field of a header of the datagram for assignment to the wireless base station via a backbone network of the wireless mobile data communications system comprises program code for transmitting the datagram including the assigned port number and/or internet address to a router of the backbone network.
- 23. (Original) A computer program product according to Claim 20, wherein the assigned port number and/or internet address comprises one of a TCP port number, a UDP port number, a TP4 port number, an IP address or a CNLP address.